

KITAYGORODSKIY, YU.I.

122-3-22/30

AUTHOR: Kitaygorodskiy, Yu.I., Engineer, Kogan, M.G., Candidate of Technical Sciences, and Tuzlukova, V.A., Engineer.

TITLE: Induction Heating Installation with Step-feed Floor.
(Induktsionnyy nagrevatel' s shagayushchim podom)

PERIODICAL: Vestnik Mashinostroyeniya, 1957, No.3, pp. 57 - 58
(USSR)

ABSTRACT: In induction-heating furnaces working on the heating zone principle, the blanks to be heated are fed by a pneumatic pusher. The disadvantages of this arrangement are discussed and a machine is described which has a moving floor consisting of water-cooled tubes of heat-resisting steel tubes. It lifts a set of blanks and advances them by a step before they are again deposited on the bottom of the furnace. The kinematics of the vertical and horizontal reciprocating motions is illustrated. The main power consumptions and losses are given in a table. The specific power consumption can be reduced to 0.5 kWh/kg. There are 2 figures, 1 table and 4 Slavic references.

AVAILABLE: Library of Congress
Card 1/1

KITAYGORODSKIY Yu. I.

24-1-23/26

AUTHORS: Yerokhin, A.A., Kitaygorodskiy, Yu. I., Kogan, M. G.,
and Silin, L. L. (Moscow).

TITLE: On the effect of ultrasonics on the character of
crystallisation inside a weld pool. (O vozdeystvii
kolebaniy ul'trazvukovoy chastoty na kharakter
kristallizatsii svarочноy vannы).

PERIODICAL: Izvestiya Akademii Nauk, Otdeleniye Tekhnicheskikh
Nauk, 1958, No.1, pp. 140-142 (USSR).

ABSTRACT: The results are described of some tests carried out
by the Institute of Metallurgy, Ac.Sc. USSR (Institut
Metallurgii AN SSSR) and the Scientific Research
Technological Institute (Nauchno-Issledovatel'skiy
Tekhnologicheskii Institut) on the effects of ultra-
sonics on the character of crystallisation of the metal
under welding conditions, paying particular attention to
welding of scale resistant austenitic steels for which
the problem of improving the structure is of particular
interest in view of their pronounced tendency to trans-
crystallisation. Typical welding equipment and standard
welding regimes were used. Automatic welding was
effected under flux, argon arc welding was effected by
means of a tungsten electrode of 5 mm dia. using as

Card 1/3

24-1-23/26

On the effect of ultrasonics on the character of crystallisation inside a weld pool.

metal
addition/4 mm wire of the alloy ~~3M~~-334. The oscillations in the metal were generated by means of a magnetostriction element which was rigidly connected to the transducer. The natural frequency of the mechanical system in the no-load state equalled 19.5 kc/sec, which varied as a function of the temperature of the metal, the dimensions of the bath and other factors, by 0.5 to 1.5 kc/sec when the bath was filled. The amplitude was about 35 μ . Preliminary calculations showed that such an amplitude ensures a kinetic energy which is adequate for influencing effectively the crystallisation of the weld joint. The power consumed by the transducer is 2 to 2.5 kW. Two methods of generating the oscillations are compared; in one the oscillations were transmitted to the bath through the base metal (Fig.1a), whilst in the other the oscillations were produced in the weld pool itself by means of direct submersion of the tip of the oscillating element into the molten pool. The second mentioned method proved more favourable. The carried out experiments proved the possibility of utilisation of ultrasonics for

Card 2/3

On the effect of ultrasonics on the character of crystallisation
inside a weld pool.

24-1-23/26

controlling the processes of crystallisation of the metal
of the seam during fusion welding.

There are 4 figures and 3 references - 1 Russian,
1 English, 1 German.

SUBMITTED: October 5, 1957.

AVAILABLE: Library of Congress.

Card 3/3

KITAYGORODSKIY, Yu. I., inzh; KOGAN, M. G., kand. tekhn. nauk (Moskva).

Generator for energizing large magnetostrictive transducers. Elektrichesvo no. 2167-69 Y '58. (NIRA 11:2)
(Transducers)

SOV/122-58-7-13/21

AUTHORS: ~~Kitaygeredskiy, Yu. I.~~, Engineer and Kogan, M.G., Candidate of Technical Sciences

TITLE: The Modernisation of High-frequency Tube Oscillators
(Modernizatsiya lampovykh ustanovok T.V.Ch)

PERIODICAL: Vestnik Mashinostroyeniya, 1958, Nr 7, pp 42-44 (USSR)

ABSTRACT: Modernisation schemes for existing high-frequency generators have been developed and practically tested by Nauchno-issledovatel'skiy tekhnologicheskii institut (Scientific Production Research Institute). Modernised condenser batteries for the oscillator circuit can be carried out in two variants. A 7 000 μF battery consists of 14 ceramic high-frequency condensers, KVKG-3, of 1 000 μF each, parallel-series connected, and cooled by natural convection of air. In the second variant, 15 000 μF are assembled in 14 condensers of 2 200 μF each. Measures against radio interference involving filters and screening have not always been effective and the reduction in the basic frequency of the installation to 130 kc/s is recommended. Voltage stabilisers of the electronic-thyratron type and of the auto-transformer type (SAN-3 or ST-80) have been compared. In the former, mercury type thyratrons were replaced by

Card1/3

The Modernisation of High-frequency SOV/122-58-7-13/31
Tube Oscillators

gas-filled units (TG1-2.5/10) with a wider range of operating temperatures. The ST-80 stabiliser is recommended when the heating circuit is not stabilised. An excitation voltage regulator has been developed to accomplish a smooth variation in operation of the grid supply. The upper terminal of the oscillating circuit coil is connected to the valve grids, the lower terminal to the anodes. The cathode (the neutral point of the circuit) is connected to sliding contacts moving along the coils of the grid connection. Thus, in regulating the anode voltage, the neutral point of the coil changes its position. Figure 3 shows an installation for exciting and interrupting the oscillations, developed to replace the older device which incorporated special rectifiers of inadequate reliability. Oscillations are interrupted by blocking the valve. The voltage shift required is picked off a voltage divider connected in the anode supply circuit. The control is accomplished by magnetic starters which short-circuit one of the resistances in the voltage divider. In a new water-cooling installation, the older rubber hoses have been replaced by porcelain tubes of 8 mm i.d., 2 mm wall thickness and 500 mm length. Since

Card2/3

SOV/122-58-7-13/31

The Modernisation of High-frequency Tube Oscillators

electrolytic action is inevitable, replaceable copper tubes are connected in the water circuit, which have the anode potential. Electrolytic action concentrates on the copper tubes.

There are 3 figures.

Card 3/3

SOV/24-58-8-14/37

AUTHORS: ~~Kitaygorodskiy~~, Yu. I., Kogan, M. G., Kuznetsova, V. A.,
Rykalin, N. N. and Silin, L. L. (Moscow)

TITLE: Joining Metals in the Solid State by subjecting
them to the Effects of Ultrasonics (Soyedineniye
metallov v tverdom sostoyanii pri vozdeystvii
ul'trazvukovykh kolebaniy)

PERIODICAL: Izvestiya Akademii Nauk SSSR, Otdeleniye Tekhnicheskikh
Nauk, 1958, Nr 8, pp 88-90 (USSR)

ABSTRACT: During 1957 and 1958 methods of obtaining spot and seam
joints of various metals under the effect of ultrasonics
were tried out at the Institute of Metallurgy, Ac.Sc., USSR.
It was established that the quality of the obtained joints
depends on two groups of inter-related factors. The first
group of factors depends on the physical properties of the
metals (mainly hardness and ductility), the state of the
surface (presence of oxide and adsorption films, height
of micro non-uniformities) and the thickness of the joined
components. The second group of factors depends on the
regimes of the apparatus (oscillation amplitude of the
tool, effect duration, the magnitude of the contact force),
the geometry and the properties of the contact surface of

Card 1/6

SOV/24-58-8-14/37

Joining Metals in the Solid State by Subjecting them
to the Effects of Ultrasonics

the used tool. By means of ultrasonics joints of various metals and alloys were produced, e.g. copper, aluminium, 0.1 to 1.5 mm thick duraluminium and 0.2 to 0.7 mm thick standard steels. The possibility of obtaining joints depends only on the thickness of that component which is located at the side of contact with the excitor of the ultrasonics; the thickness of the other component is of no consequence. Preliminary preparation of the joined surfaces usually consists of degreasing by means of solvents (e.g. methanol). The electric power consumed by the magnetostriction transducer is between the limits of 0.7 and 2.5 kW, the ultrasonics frequency is 18 to 25 kc/sec, the amplitude of the front face of the tool is 10 to 40 μ . The duration of the effect of the ultrasonics in the case of a spot joint varied between 0.5 and 4.0 sec, the contact pressure being 10 to 100 kg, which is considerably less than the force required for cold welding by applying pressure. The optimum value of each of the parameters

Card 2/6 involved in the formation of a joint was determined by

SOV/24-58-8-14/37

**Joining Metals in the Solid State by Subjecting them
to the Effects of Ultrasonics**

maintaining constant the values of the other parameters involved. For instance, using a contact end piece of 8 mm², the optimum values of the time of applying elastic oscillations and the contact pressure were 1.5 sec and 30 kg respectively for aluminium sheet. In Fig.1 the dependence on the duration of the ultrasonics and on the contact force is graphed of the shear strength of a spot joint of a 0.5 mm thick aluminium sheet. In shear tests of such joints, the failure occurred in the base metal and not in the joint. Reduction of the duration of the ultrasonics and reduction of the contact force bring about at first only a slight reduction in the strength without reducing the zone of the actual joint. However, further reduction of these values brings about a decrease in the joint area and consequently also a decrease in the shear strength. For instance, for an ultrasonics duration of 0.5 sec and a contact force of 10 kg, the failure will occur at the contact surface; under such a regime a joint will form only in individual insignificant sections of the area. An increase of the

Card 3/6

SOV/24-58-8-14/37

**Joining Metals in the Solid State by subjecting them
to the Effects of Ultrasonics**

effect duration to 2 secs will also bring about a decrease in the strength. This is obviously associated with the longer duration of the ultrasonics which brings about an appreciable disruption of the surface layers, weakening the joints and tearing out the spot from the base metal. Tensile tests of good quality joints have shown that their strength is satisfactory, amounting to 30-35% of the shear strength. For usually applied contact forces, durations and amplitudes of the elastic oscillations, the relative deformation of the surface layers does not exceed 5%. A considerable deformation is observed only directly in the region of the joint. As an example, Fig.2 shows micro-photographs of the zones of joints of copper sheets for oscillation amplitudes of 50 μ , a contact force of 50 kg and an application time of 1.6 sec; the reproduced micro-photographs show that in the zone of the joint the deformation of the metal is very complex. Usually two main types of joint structure are observed: a peculiar vortex structure (Fig.2, top) with a mutual penetration of both of the components to be

Card 4/6

SOV/24-58-8-14/37

Joining Metals in the Solid State by subjecting them to the Effects of Ultrasonics

joined and sections with a continuous transition from one component to the other (Fig.2, centre). The thickness of the vortex structure zone reaches 0.4 mm and apparently is located at sections of the initial contact of the components to be joined. The structure of the second type occupies the larger area of the joint extending to a thickness of 0.1 to 0.15 mm and represents a zone with an almost uniform fine grain structure, whereby in the individual sections which are located in the middle of the joint it was not possible to detect a crystalline structure of the metal even if large amplifications are used (Fig.2, bottom). Micro investigations of the joint zone does not reveal an appreciable thermal effect on the structure of the metals. Micro investigations of the joint after annealing for ten minutes at 600°C revealed differing grain sizes in the base metal and in the joint zone (Fig.3). There is reason to assume that the particles of surface oxides and of adsorbed films which penetrate into the metal prevent to a certain extent selective recrystallisation, which leads

Card 5/6

SOV/24-58-8-14/37

**Joining Metals in the Solid State by subjecting them
to the Effects of Ultrasonics**

to the formation of a fine grain structure at the location of the joint. The method of joining metals in the solid state by means of ultrasonics is applicable not only to the here mentioned materials. At present investigations are being carried out relating to the conditions of formation of joints for a wider group of metals and alloys and the apparatus to be used for such work is being developed.

There are three figures.

(Note: This is a complete translation)

SUBMITTED: April 4, 1958

1. Metals--Bonding
2. Metals--Properties
3. Ultrasonic radiation--Performance
4. Ultrasonic radiation--Metallurgical effects
5. Ultrasonic projectors--Performance

Card 6/6

KITAYGORODSKIY, Yu.I., inzh.; KOGAN, M.G., kand. tekhn. nauk; BELOUSOV, N.A.,
inzh.

Using high-frequency electron-tube oscillators in exciting powerful
ultrasonic oscillations. Vest. mash. 38 no.3:33-34 Nr '58.
(Oscillators, Electron-tube) (Ultrasonic waves) (MIRA 11:2)

KITAYGORODSKIY, Yu.I., inzh.; KOZAN, M.G., kand.tekhn.nauk

Modernising installations having r-f current tubes. Vest.mash.
38 no.7:42-44 J1 '58. (MIRA 11:8)
(Electronic apparatus and appliances)

KITAYGORODSKIY Yu.

PHASE 1 BOOK EXPLANATION 207/3538

Books. See numbers-tables/number propagation
 Principles of ultrasonic propagation; Special strategy (De-
 tecting the use of ultrasonic); Collection of articles) Moscow,
 Nauka, 1979. 301 p. 8,000 copies printed.
 1 monograph study USSR.
 M. (Title page): V.P. Buzov, Doctor of Physical and Mathematical
 Sciences, Professor; M. (Inside book): G.P. Koshov, Engineer;
 Tash. M.: V.P. Buzov, Managing Ed. For literature on Machinery
 and Instrument Manufacturing (Machin.) M.V. Polovnikov, Engineer.
 PREFACE: This book is intended for engineers and technicians engaged
 in the application of ultrasonics in machinery manufacture and in
 other branches of industry.
 CONTENTS: This is a collection of papers read at the first all-
 union conference on the use of ultrasonics in industry. Attention
 is focused mainly on the methods of ultrasonic equipment and
 on the use of ultrasonic effect of ultrasonic on metal crystalli-
 zation processes in the dissolved. No personalization are mentioned.
 References accompany many of the papers.
 Bibliography: V.P. Buzov, Engineer and R.G. Yagor, Candidate of Sci-
 ences, Engineer. Ultrasonic Equipment for Industrial Applica-
 tions
 Moscow, U.S.S.R., Candidate of Technical Sciences, Doctor. Design
 and Construction of Ultrasonic for Ultrasonic Machines 64
 77
 Polovnikov, V.P., Candidate of Technical Sciences, M.V. Polovnikov,
 Candidate of Technical Sciences, and V.P. Buzov, Candidate
 of Technical Sciences. Negative Allergy for Ultrasonic Appli-
 cations 92
 Buzov, V.P., Engineer. Methods of Making Design Calculations 108
 109
 110
 111
 112
 113
 114
 115
 116
 117
 118
 119
 120
 121
 122
 123
 124
 125
 126
 127
 128
 129
 130
 131
 132
 133
 134
 135
 136
 137
 138
 139
 140
 141
 142
 143
 144
 145
 146
 147
 148
 149
 150
 151
 152
 153
 154
 155
 156
 157
 158
 159
 160
 161
 162
 163
 164
 165
 166
 167
 168
 169
 170
 171
 172
 173
 174
 175
 176
 177
 178
 179
 180
 181
 182
 183
 184
 185
 186
 187
 188
 189
 190
 191
 192
 193
 194
 195
 196
 197
 198
 199
 200
 201
 202
 203
 204
 205
 206
 207
 208
 209
 210
 211
 212
 213
 214
 215
 216
 217
 218
 219
 220
 221
 222
 223
 224
 225
 226
 227
 228
 229
 230
 231
 232
 233
 234
 235
 236
 237
 238
 239
 240
 241
 242
 243
 244
 245
 246
 247
 248
 249
 250
 251
 252
 253
 254
 255
 256
 257
 258
 259
 260
 261
 262
 263
 264
 265
 266
 267
 268
 269
 270
 271
 272
 273
 274
 275
 276
 277
 278
 279
 280
 281
 282
 283
 284
 285
 286
 287
 288
 289
 290
 291
 292
 293
 294
 295
 296
 297
 298
 299
 300
 301
 302
 303
 304
 305
 306
 307
 308
 309
 310
 311
 312
 313
 314
 315
 316
 317
 318
 319
 320
 321
 322
 323
 324
 325
 326
 327
 328
 329
 330
 331
 332
 333
 334
 335
 336
 337
 338
 339
 340
 341
 342
 343
 344
 345
 346
 347
 348
 349
 350
 351
 352
 353
 354
 355
 356
 357
 358
 359
 360
 361
 362
 363
 364
 365
 366
 367
 368
 369
 370
 371
 372
 373
 374
 375
 376
 377
 378
 379
 380
 381
 382
 383
 384
 385
 386
 387
 388
 389
 390
 391
 392
 393
 394
 395
 396
 397
 398
 399
 400
 401
 402
 403
 404
 405
 406
 407
 408
 409
 410
 411
 412
 413
 414
 415
 416
 417
 418
 419
 420
 421
 422
 423
 424
 425
 426
 427
 428
 429
 430
 431
 432
 433
 434
 435
 436
 437
 438
 439
 440
 441
 442
 443
 444
 445
 446
 447
 448
 449
 450
 451
 452
 453
 454
 455
 456
 457
 458
 459
 460
 461
 462
 463
 464
 465
 466
 467
 468
 469
 470
 471
 472
 473
 474
 475
 476
 477
 478
 479
 480
 481
 482
 483
 484
 485
 486
 487
 488
 489
 490
 491
 492
 493
 494
 495
 496
 497
 498
 499
 500
 501
 502
 503
 504
 505
 506
 507
 508
 509
 510
 511
 512
 513
 514
 515
 516
 517
 518
 519
 520
 521
 522
 523
 524
 525
 526
 527
 528
 529
 530
 531
 532
 533
 534
 535
 536
 537
 538
 539
 540
 541
 542
 543
 544
 545
 546
 547
 548
 549
 550
 551
 552
 553
 554
 555
 556
 557
 558
 559
 560
 561
 562
 563
 564
 565
 566
 567
 568
 569
 570
 571
 572
 573
 574
 575
 576
 577
 578
 579
 580
 581
 582
 583
 584
 585
 586
 587
 588
 589
 590
 591
 592
 593
 594
 595
 596
 597
 598
 599
 600
 601
 602
 603
 604
 605
 606
 607
 608
 609
 610
 611
 612
 613
 614
 615
 616
 617
 618
 619
 620
 621
 622
 623
 624
 625
 626
 627
 628
 629
 630
 631
 632
 633
 634
 635
 636
 637
 638
 639
 640
 641
 642
 643
 644
 645
 646
 647
 648
 649
 650
 651
 652
 653
 654
 655
 656
 657
 658
 659
 660
 661
 662
 663
 664
 665
 666
 667
 668
 669
 670
 671
 672
 673
 674
 675
 676
 677
 678
 679
 680
 681
 682
 683
 684
 685
 686
 687
 688
 689
 690
 691
 692
 693
 694
 695
 696
 697
 698
 699
 700
 701
 702
 703
 704
 705
 706
 707
 708
 709
 710
 711
 712
 713
 714
 715
 716
 717
 718
 719
 720
 721
 722
 723
 724
 725
 726
 727
 728
 729
 730
 731
 732
 733
 734
 735
 736
 737
 738
 739
 740
 741
 742
 743
 744
 745
 746
 747
 748
 749
 750
 751
 752
 753
 754
 755
 756
 757
 758
 759
 760
 761
 762
 763
 764
 765
 766
 767
 768
 769
 770
 771
 772
 773
 774
 775
 776
 777
 778
 779
 780
 781
 782
 783
 784
 785
 786
 787
 788
 789
 790
 791
 792
 793
 794
 795
 796
 797
 798
 799
 800
 801
 802
 803
 804
 805
 806
 807
 808
 809
 810
 811
 812
 813
 814
 815
 816
 817
 818
 819
 820
 821
 822
 823
 824
 825
 826
 827
 828
 829
 830
 831
 832
 833
 834
 835
 836
 837
 838
 839
 840
 841
 842
 843
 844
 845
 846
 847
 848
 849
 850
 851
 852
 853
 854
 855
 856
 857
 858
 859
 860
 861
 862
 863
 864
 865
 866
 867
 868
 869
 870
 871
 872
 873
 874
 875
 876
 877
 878
 879
 880
 881
 882
 883
 884
 885
 886
 887
 888
 889
 890
 891
 892
 893
 894
 895
 896
 897
 898
 899
 900
 901
 902
 903
 904
 905
 906
 907
 908
 909
 910
 911
 912
 913
 914
 915
 916
 917
 918
 919
 920
 921
 922
 923
 924
 925
 926
 927
 928
 929
 930
 931
 932
 933
 934
 935
 936
 937
 938
 939
 940
 941
 942
 943
 944
 945
 946
 947
 948
 949
 950
 951
 952
 953
 954
 955
 956
 957
 958
 959
 960
 961
 962
 963
 964
 965
 966
 967
 968
 969
 970
 971
 972
 973
 974
 975
 976
 977
 978
 979
 980
 981
 982
 983
 984
 985
 986
 987
 988
 989
 990
 991
 992
 993
 994
 995
 996
 997
 998
 999
 1000

28(4)

AUTHORS:

SOV/32-25-4-40/71

Kitaygorodskiy, Yu. I., Bogin, V. S., Vitkovskiy, A. V.

TITLE:

Ultrasonic Generator for Laboratory Tests (Ul'trazvukovoy generator dlya laboratornykh issledovaniy)

PERIODICAL:

Zavodskaya Laboratoriya, 1959, Vol 25, Nr 4, pp 477-478 (USSR)

ABSTRACT:

A generator UZG-3 was designed for laboratory tests in the field of industrial application of ultrasonics. The generator is calculated for an efficiency of 3 kw and a consumption capacity of 5 kw (supply with 220 v single-phase line current). It works in a frequency range of from 3 to 300 cycles continuously or in pulses. The pulses can be regulated in the range of from 30 to 1000 μ sec, and the repetition frequency from 20 to 10000 cycles. A diagram of the generator is given (Figure) which shows that the individual parts - the generator, the voltage amplifier, the pulse modulator, the capacity amplifier and adjustable magnetizing rectifiers - are supplied separately. The description of the device says, among other things, that the above-mentioned capacity amplifier serves as an output circuit of the generator UZG-3 which is composed of a push-pull circuit with the tubes 6U-80. The generator is used in investigations of different technological processes with an action of

Card 1/2

SOV/32-25-4-40/71

Ultrasonic Generator for Laboratory Tests

oscillations of ultrasonic frequency, such as in purifications, mechanical treatment of hard and brittle materials, metal crystallisations, etc. There is 1 figure.

Card 2/2

KITAYGORODSKIY, Yu.I.

"The present State and Trend of Development of the Technological
Application of Ultrasonics in Mechanical Engineering."

report presented at the All-Union Scientific-Engineering Conference on the
Application of Ultrasonics in Industry, Moscow, 22-26 November 1960.

24,1800

S/194/62/000/005/080/157
D222/D309

AUTHOR: Kitaygorodskiy, Yu.I.

TITLE: Industrial ultrasound generators and transducers

PERIODICAL: Referativnyy zhurnal. Avtomatika i radioelektronika,
no. 5, 1962, abstract 5-5-34 ch (V sb. Primeneniye
ul'trazvuka v tekhnol. mashinostr. no. 2, M., 1960,
3 - 14)

TEXT: The circuit diagrams and constructional design of the $\gamma 3P$ (UZG) series of ultrasound generators of 2.5, 5, 10, and 20 kW output power are described. The results of investigating various magnetostrictive transducers are given. The efficiency of the ПМС-6 (PMS-6) transducer, of transducers made of the alloys K49 $\phi 2$ (K49 P2). $\phi 14$ (Yu14), and also the dependence of the specific power of different kinds of transducers on the induction were investigated. The electrical characteristics of different transducers and their geometrical dimensions are also given. [Abstractor's note: Complete translation].

Card 1/1

3/575/62/000/007/007/016
A004/A1011-195.
AUTHORS:Kaluzhinova, I. S., Kitaygorodskiy, Yu. I.

TITLE:

Investigating the factors affecting ultrasonic cleaning processes

PERIODICAL:

Referativnyy zhurnal, Mashinostroyeniye, no. 7, 1962, 31, abstract
7B168 (V sb. "Primeneniye ul'trazvuka v tekhnol. mashinostr.", no.2,
Moscow, 1960, 75-83)

TEXT:

The authors present the results of investigating the dependence of ultrasonic cleaning duration on the distance of the specimens from the emitting surface of standard ΠMC (PMS) converters. The tests were carried out in the $Y3B-2$ (UZV-2) baths supplied by a $Y3T-10$ (UZO-10) generator on flat ground specimens of stainless $1X18H9T$ ($1Kh18H9T$) grade steel, 100 x 100 mm and 100 mm in diameter, having a thickness of 0.8, 3 and 5 mm. The degreasing solution had the composition (g/l): sodiumtripphosphate, calcined soda - 3 and $OP-10$ (OP-10) - 3 at 45 - 50°C. It was found that the duration of cleaning grows with the distance of the specimen from the surface up to a certain magnitude (at a distance of 80 - 90 mm and more, the cleaning time remained practically unchanged). The lower the oscillation intensity of the converter (being determined by the

Card 1/4

S/123/62/000/007/016
A004/A101

Investigating the factors affecting ...

applied voltage) the shorter the distance in whose limits the position of the specimen affects the cleaning time. Increasing the specimen thickness up to 5 mm and reducing the voltage from 520 to 110 v noticeably affects the degreasing duration only if the part is placed in immediate proximity to the converter. At a short distance of the specimen from the converter surface, the cleaning duration of the specimen lower surface is considerably shorter than that of the upper one. If the specimen is removed from the bath bottom, the cleaning time of the upper and lower surfaces almost did not change. Flat plates of 30 x 80 mm were used for the cleaning from slime, the plates being cut out from 1X18N8T sheet steel of 0.8, 2 and 2.5 mm thickness with scale after heat treatment (water-quenching at 1,050 - 1,100°C). The scale was preliminarily pickled with-out ultrasonics in a solution with 100 - 120 ml/l nitric acid (density - 1.35) and 45 g/l sodium fluoride at 40 - 45°C. The specimens of 0.8 mm thickness were pickled for 10 min, those of 2 mm thickness for 15 min, and the 2.5 mm specimens were pickled for 35 min. The slime was removed immediately after holding in the pickling solution. All tests for removing the slime were carried out with slight swinging of the specimens. Tests were also carried out for cleaning blind holes 1 - 5 mm in diameter and 30 - 35 mm deep on aluminum-alloy parts of intricate configuration with the dimensions 400 x 300 x 50 and 400 x 330 x 40 mm,

Card 2/4

5/123/62/000/007/007/016
A004/A101

Investigating the factors affecting ...

with projecting parts up to 120 - 130 mm high. Cleaning was effected in a solution containing sodiumtriphosphate, calcined soda and OP-10 by 3 g/l each at 50°C and in "Galosha" gasoline at 20 - 30°C using ultrasonics. The authors report on the cleaning of deep through channels in large-size parts of 500 x 300 x 200 mm, the channel diameter being 100 mm and the depth 200 mm. The parts were cleaned in an ultrasonic bath and in a 30 g/l sodiumtriphosphate solution to which 3 g/l OP-10 were added at 50°C. Cleaning of the parts in the ultrasonic bath proved to be inefficient. An analysis of the obtained results revealed that for an efficient cleaning of the outer surfaces of parts, they have to be placed as near as possible to the converter surface. For cleaning the outer surfaces of voluminous parts, they have to be revolved in the ultrasonic bath, or baths have to be used in which converters are not only placed on the bottom, but also on the side walls. A swinging of the specimens during the treatment increases the homogeneity of cleaning over its entire surfaces. The most efficient method of transmitting ultrasonic oscillations during the cleaning of deep channels in solid thick-walled parts is to introduce the tool in the aperture. Investigations of the effect of ultrasonics on the acceleration of the pickling process, which were carried out on specimens and parts from 1Kh18N9T and CH 2 20 (SN2 20) steel and OT 4 and BT 1 (VT 1) titanium alloys in the form of flat

Card 3/4

Investigating the factors affecting ...

S/123/62/000/007/007/016
A004/A101

plates and nipples, showed that ultrasonic waves accelerate the pickling process by a factor of 2 - 3, and also promote the removal of secondary pickling products (slime) from the metal surface, moreover, the surface finish of the treated metal is improved. It is pointed out that, in solving the problem of expediency of using ultrasonics in the pickling process it is necessary to take into account that an acceleration of the process by a factor of 2 - 3 is an insufficient characteristic of the efficiency of using ultrasonics. Its application is necessary for improving the surface finish and the quality of the parts.

[Abstractor's note: Complete translation]

Card 4/4

S/137/62/000/004/181/201
A154/A101

AUTHORS: Olizburg, I.L., Kitaygorodskiy, Yu.I., Krasnov, I.I.,
Radzeyevskaya, Ye.V., Sysolin, O.V.

TITLE: Ultrasonic welders

PERIODICAL: Referativnyy zhurnal, Metallurgiya, no. 4, 1962, 71, abstract
4B398 (Sb. "Primeneniye ul'trazvuka v tekhnol. mashinostr."
no. 2, M., 1960, 162 - 170)

TEXT: A detailed examination was made of the design of the following
ultrasonic welders: the Y3CM-1 (UZSM-1) for spot-welding sheet metal; the
Y3CA-3 (UZSA-3) for welding sheet parts in structures with large planes or
profiled surfaces; the Y3CA-4 (UZSA-4) for spot-welding sheet parts in large
items; the Y3CM-2 (UZSM-2) for seam-welding sheet metal. The technical charac-
teristics of each welder are given.

V. Tarisova

[Abstracter's note: Complete translation]

Card 1/1

KITAYGORODSKIY, Yu. I.

"Economy of the ultrasonic apparatus."

report presented at the Intl Symp on Ultrasonics Application, Bratislava, C88R, 6-12
Sep 62.

L 57536-65 EWT(m)/EWP(w)/EPF(c)/EPT(n)-2/EWA(d)/T/EWP(t)/EWP(z)/EWP(b)/
 EWA(h)/EWA(-) Pad/Peb/Pu-L IJP(c) MJW/JJ, JW/JJ, WB
 ACCESSION NR: AR5015182 UR/0137/65/000/005/1037/1037

SOURCE: Ref. zh. Metallurgiya, Abs. 51235

AUTHOR: Agrazat, B. A.; Baghirov, V. I.; Kitaygorodskiy, Yu. I.

1. Cavitation failure of metals and alloys in an ultrasonic field

CITED SOURCE: Sb. Primeneniye ul'trazvuka v mashinostr. Minsk. Nauka i tekhnika, 1964, 89-93

TOPIC TAGS: tantalum, rhenium, cobalt, molybdenum, chromium, columbium, steel, cavitation resistance, corrosion resistance, water, sulfuric acid, ultrasonic field/ Kh18N9T steel, BRAZh

TRANSLATION: An experimental study was made of the corrosion-cavitation resistance of a number of metals and alloys (tantalum, rhenium, cobalt, molybdenum, BRAZh Mts-10-3-1.5, Kh18N9T steel, chromium, columbium). The preliminary tests were carried out in a 20% solution of H_2SO_4 at a pressure of 5 atm and at an amplitude of sound pressure approximately equal to 5 atm (to intensify cavitation failure by the accelerated impact of cavitation bubbles). Among the materials investigated, BRAZh had the greatest resistance. A

Card 1/2

L 57536-65

ACCESSION NR: AR5015182

metallographic analysis ^{to} is given. V. Geminov.

SUB CODE: 104

ENCL: 00

dm
Card 2/2

L-10555-66 EWT(1)/EWT(M)/EWA(d)/T/EWP(t)/EWP(x)/EWP(z)/EWP(b)/EWA(h) NJW/JD
ACC NR: AR5018643 SOURCE CODE: UR/0275/65/000/007/V009/V010

SOURCE: Ref. zh. Elektronika i yeye primeneniye. Svochnyy tom, Abs. 7V73

AUTHOR: Agranat, B. A.; Bashkirov, V. I.; Kitaygorodskiy, Yu. I.

TITLE: Cavitation damage to metals and alloys in ultrasonic fields

CITED SOURCE: Sb. Primeneniye ul'trasvuka v mashinostr. Minsk, Nauka i tekhnika, 1964, 89-93

TOPIC TAGS: ultrasonics, metal test, corrosion resistance, metal surface, fabricated structural metal, ultrasonic field, ultrasonic effect, bronze, metal

TRANSLATION: Metals having higher cavitation and corrosion resistance were investigated as materials for building radiators and entrances in the ultrasonic-etching baths for transformer steel. First, the cavitation resistance in water was determined, and then the best metals were tested in a 20% H₂SO₄ at a pressure of 5 atm, in an enclosed chamber, with an ultrasonic pressure amplitude of 8 atm.

Card 1/2

UDC: 534.29-8

L 10555-66

ACC NR: AR5018643

2

In the latter case, the process was much intensified due to a higher speed of closing the bubbles during the compression half-cycle, which resulted in speedy destruction of the metals. Corrosion resistance of 50x70x8 radiators soldered to a magnetostriction packet was tested in a 20% H_2SO_4 , at 60C, with an ultrasonic application of 7 hours a day. The results were: Ta, 16 hours; Ti, 14 hours; Mo, 52 hours. The best results were obtained with the BrAZhMTs-10-3-1,5 bronze (150 hours); this bronze has been selected for producing industrial prototypes of converters having a uniform ultrasonic field and intended for etching work in metallurgical plants.

SUB CODE: 11, 20, 13

Cord 2/2 pu

KITAYNIK, A.

It is good to be a businessman. Grashd. av. no.3:22-23 Mr '61.
(MIRA 14:3)
(Novosibirsk--Aeronautics, Commercial)

GLEMBOTSKIY, Ya.L., kand. sel'khoz. nauk, otv. red.; KITAYNIK, A.U.,
red.

[Judging and selecting herd rams of the Altai fine-wool
breed] Otsenka i otbor proizvoditelei Altaiskoi tonkorunnoi
porody. Novosibirsk, Nauka, 1965. 158 p. (MIRA 19:1)

1. Akademiya nauk SSSR. Sibirskoye otdeleniye.

KITAYNIK, ABRAHAM, USHEROVICH.

SHEPELEV, Aleksandr Origor'yevich, ASHCHEPKOV, Yevgeniy Andreyevich;
KOZHEVNIKOV, Savva Yelizarovich; NEMIRA, Kirill L'vovich; KITAYNIK,
Abram Usherovich; SINAGOV, V.E., red.; MAZUROVA, A.P., tekhn.red.

[With our friends; impressions of Siberians visiting people's
democracies] U Nashikh druzel; vpechatleniia sibiriakov, pobывavshikh
v stranakh narodnoi demokratii. [Novosibirsk] Novosibirskoe knizhnoe
izd-vo, 1957. 127 p. (MIRA 10:12)

(China--Description and travel)

(Czechoslovakia--Description and travel)

(Germany, East--Description and travel)

PONOMAREV, P.A.; KITAYNIK, A.U., red.; SUBBOTINA, O.M., tekhn. red.

[Siberian strides] Shagami sibirskimi. Novosibirsk, Novosibirskoe knishnoe izd-vo, 1961. 250 p. (MIRA 15:6)
(Siberia—Industries)

KASIMENSKAYA, Ol'ga Vadinovna; KHVOROSTOVA, Zoya Mikhaylovna;
KITAYNIK, A.U., red.

[Geomorphological analysis in prospecting for placers
(based on a study of the El'gi gold-bearing region in the
upper Indigirka Valley)] Geomorfologicheskii analiz pri
poiskakh rossypei (na primere El'ginakogo zolotonosnogo
raiona v verkhov'iyakh reki Indigirki. Novosibirsk, Red.-
izd. otdel Sibirskogo otd-niia AN SSSR, 1965. 165 p.
(MIRA 18:6)

KHOKHLOVICH, David Mikheylovich; KITAYSKIY, S.V., otvetstvennyy redaktor;
SAVIN, M.M., redaktor izdatel'stva; KOROVENKOVA, Z.A., tekhnicheskii
redaktor

[Evacuating water in the sinking of vertical mine shafts] Vodootliv
pri provedenii vertikal'nykh stvolov shakht. Moskva, Ugletekhnizdat,
1956. 130 p. (MIRA 10:1)

(Pumping machinery) (Shaft sinking)

POBEREZHIN, Ye.A., dotsent; KIRICHINSKIY, M.R., otvetstvennyy redaktor;
KITAYSKIY, Ye.V., redaktor; SHPAK, Ye.O., tekhnicheskiy redaktor.

[Efficient calculation of continuous beams] Ratsionalizatsiya
rascheta nerasresnykh balok] Pt. 2. [Beams with differing linear
rigidity in all spans] Balki s raznymi pogonnymi shestkostiami vo
vsekh proletakh. Moskva, Ugletekhnizdat. 1952. 214 p. [Microfilm]
(Girders) (MLBA 8:1)

FEDOROV, S.A.; PAYLOV, K.V., otvetstvennyy redaktor; KITAYSKIY, Ye.Y.,
redaktor; PROZOROVSKAYA, V.L., tekhnicheskii redaktor

[Sinking and deepening vertical mine shafts by the regular method]
Prokhodka i uglubka vertikal'nykh stvolov shakht obychnym sposobom.
Moskva, Ugletekhnizdat, 1954. 491 p. [Microfilm] (MLRA 8:4)
(Shaft sinking)

CHIKRIBOVYKH, Mikhail Inokent'yevich; KITAYSKIY, Ye.V., redaktor; PROZOROV-
SKAYA, V.L., tekhnicheskii redaktor

[Pneumatic loaders of the BCh type] Pnevmaticheskie gruzchiki tipa
BCh. Moskva, Ugletekhnizdat, 1955. 27 p. (MIRA 9:1)
(Coal-handling machinery)

KITAYSKIY, Ye.V.

CHUPRUNOV, Grigoriy Dmitriyevich, kandidat tekhnicheskikh nauk; KITAY-
SKIY, Ye.V., redaktor; KOROVIKOVA, Z.A., tekhnicheskij redaktor;
IL'YASKAYA, G.M., tekhnicheskij redaktor.

[Boring first holes in sinking vertical mine shafts] Burenie
shpurov pri prokhodke vertikal'nykh stvolov shakht. Moskva,
Ugletekhnizdat, 1955. 37 p. (MLRA 8:11)
(Shaft sinking)

SAMOYLOVSKIY, M.B., otvetstvennyy redaktor; **KITAYSKIY, Ye.V.**, redaktor
izdatel'stva; **ALADOVA, Ye.I.**, tekhnicheskij redaktor; **KADNINSKAYA,**
A.A., tekhnicheskij redaktor

[Organisation diagrams for working horizontal and inclined shafts)
Skhemy organizatsii provedeniya gorizonta'lnykh i naklona'nykh
gorn'nykh vyrabotok. Moskva, Ugletekhizdat, 1955. 143 l. (MLRA 9:9)
[Microfilm]

1. Khar'kov. Vsesoyuznyy nauchno-issledovatel'skiy institut
organizatsii i mekhanizatsii shakhtnogo stroitel'stva.
(Coal mines and mining)

KITAYSKIY, Ye.V.

MINDLI, Elisbar Onisipovich, kandidat tekhnicheskikh nauk; ASSONOV,
V.A., redaktor; KITAYSKIY, Ye.V., redaktor; PROZOROVSKAYA, V.L.
tekhnicheskii redaktor.

[Analysis of boring and blasting operations in the sinking of
vertical mine shafts] Analiz buro-vzryvnykh rabot pri prokhodke
vertikal'nykh stvolov shakht. Moskva, Ugletekhnizdat, 1955. 258 p.
(Shaft sinking)

SAMOYLOVSKIY, M.B., redaktor; KITAYSKIY, Ye.V., redaktor; MADUNSKAYA, A.A.
tekhnicheskii redaktor; KOSOVENKOVA, E.A., tekhnicheskii redaktor.

[Studies in the construction of shafts] Issledovaniia po shakhtnomu
stroitel'stvu. Moskva, Ugletekhnizdat, 1955.274 p. (MLRA 9:4)

1. Khar'kov. Vsesoyuznyy nauchno-issledovatel'skiy institut organi-
zatsii i mekhanizatsii shakhtnogo stroitel'stva.
(Shaft sinking)

POKROVSKIY, Nikolay Mikhaylovich, professor, doktor tekhnicheskikh nauk;
KITAYSKIY, Ye.V., redaktor; SAVIN, M.M., redaktor; ALADOVA, Ye.I.,
~~tekhnicheskii~~ redaktor.

[Mining engineering on horizontal and inclined planes] Provedenie
gorizontal'nykh i naklonnykh gornykh vyrabotok. Izd. 2-e, perer.i
dop. Moskva, Ugletekhnizdat, 1955. 363 p. (MLRA 9:4)
(Mining engineering)

POSEVIN, Pantelaymon Stepanovich; KITAYSKIY, Ye. V., otvetstvennyy redaktor;
SMIRNOV, L.V., redaktor izdatel'stva; KOROVNIKOVA, Z.A., tekhnicheskiy redaktor

[Operator of the BCh-1 pneumatic loader in mines] Prokhodchik-mashinist pnevmaticheskogo grushnika BCh-1. Moskva, Ugletekhnizdat, 1956.
149 p. (MIRA 10:3)

(Mining machinery)

KITAYSKIY, YE. V.

LI CHAO-TSYUN' [Li, Ch'ao-Chun]; NASOKOV, Leonid Nikolayevich; KITAYSKIY
Ye.V., otvetstvennyy redaktor; KRASOVSKIY, I.P., redaktor izdatel'-
stva; ANDRIYEV, O.G., tekhnicheskiy redaktor; ALADOVA, Ye.I.,
tekhnicheskiy redaktor

[Mining in the Chinese People's Republic] Opyt provedeniya gornykh
vyrabotok v Kitaiskoi Narodnoi Respublike. Moskva, Ugletekhnizdat,
1957. 94 p. (MLRA 10:10)
(China--Coal mines and mining)

KRIVONOGOV, Konstantin Konstantinovich; BUGRO, Fedor Yevseyevich; KITAYSKIY,
Ye.I., otvetstvennyy red.; ZVORYKINA, L.N., red.isd-va; ALADOVA,
Ye.I., tekhn.red.

[Ways of increasing the speed of mining operations] Puti uvelicheniia
tempov provedeniia gornykh vyrabotok. Moskva, Ugletekhnizdat, 1957.
145 p. (MIRA 11:5)

(Coal mines and mining)

OKLESKUL, Mikhail Nikitich.; KITAYSKIY, Ye.V., otv. red.; KRYZHEVSKIY,
V.Ye., otv. red.; ALADOVA, Ye.I., tekhn. red.

[Metal and reinforced concrete timbering in mine workings]
Metallicheskaia i zhelezobetonnaia krep' podgotovitel'nykh
gornykh vyrabotok. Moskva, Ugletekhnizdat, 1958. 319 p. (MIRA 11:11)
(Mine timbering)

POKROVSKIY, Nikolay Mikhaylovich, prof., doktor tekhn.nauk; KITATSKIY, Ye.V.,
otv.red.; PETRAKOVA, Ye.P., red.isd-va; KOROVENKOVA, E.A., tekhn.red.

[Sinking of vertical mine shafts by the regular method] Pro-
khodka vertikal'nykh stvolov shakht obychaym sposobom. Isd.2.
Moskva, Ugletekhnizdat, 1959. 443 p. (MIRA 12:7)
(Shaft sinking)

PINES, M.Ye.; SMORODSKIY, P.V.; KITAYSKIY, Ye.V., red.; MURONETS, I.I.,
red.; BRUDNO, K.F., tekhn. red.

[German-Russian mining dictionary] Nemetsko-russkii gornyi slovar'.
Pod red. E.V. Kitaiskogo. Moskva, Glav. red. inostr. nauchno-tekhn. slo-
varei Fizmatgiz, 1961. 428 p. (MIRA 14:2)
(German language--Dictionaries--Russian)
(Mining engineering--Dictionaries)

DROGAL', Grigoriy Grigor'yevich; ALGASOV, Vladimir Stepanovich;
LYCHKO, Ivan Grigor'yevich; KITAYSKIY, Ye. V., otv. red.;
MESHCHANKINA, I. S., tekhn. red.

[Rapid crosscutting] Opyt skorostnogo provedeniia gor-
nykh vyrabotok. Moskva, 1962. 27 p. (MIRA 16:8)

1. Tsentral'nyy institut tekhnicheskoy informatsii ugol'noy
promyshlennosti.

(Coal mines and mining)

KITAYTSEV, A. M.

BURKOVSKAYA, Ye.Kh.; nauchnyy sotrudnik; IORUNOV, V.D., nauchnyy sotrudnik;
MECHAYEV, I.M., nauchnyy sotrudnik; BOBRIKOVA, V.N.; TERENT'YEVA,
T.N.; SHCHERBAKOVA, L.F.; BERLIN, I.A.; otv.red.; KITAYTSEV, A.M.,
red.; KUZ'MIN, L.A., red.; OLIMPOV, V.O., red.; SKITSEKIN, I.S.,
red.; RUSIN, M.P., red.; MARTYNOV, S.I.; red.; SIMONOV, Ya.P.,
red.; IVANOV, A.P., red.; BESSONOV, M.P., red.; YASNOGORODSKAYA,
M.M., red.; VLADIMIROV, O.O., tekhn.red.

[Directions for hydrometeorological stations and posts] Nastavlenie
gidrometeorologicheskim stantsiam i postam. Leningrad, Gidrometeor.
(Continued on next card)

BURKOVSKAYA, Ye.Kh.--(continued) Card 2.

1zd-vo. No.3, pt.2. [Working up materials of meteorological
observations] Obrabotka materialov meteorologicheskikh
nabliudenii. 1958. 85 p. (MIRA 13:1)

1. Russia (1923- U.S.S.R.) Glavnoye upravleniye gidrometeoro-
logicheskoy sluzhby. 2. Glavnaya geofizicheskaya observatoriya in.
A.I.Voyeykova (for Burkovskaya, Igrunov, Nechayev). 3. Starshiye
inzhnery Nauchno-issledovatel'skogo instituta aeroklimatologii
(for Bobrikova, Terent'yeva). 4. Glavnoye upravleniye Gidrometeo-
rologicheskoy sluzhby SSSR (for GUOMS) (for Kitaytsev, Kuz'min,
Olimpov, Skiteykin). 5. Glavnaya geofizicheskaya observatoriya (OOO)
(for Berlin, Nechayev, Rusin, Shcherbakova). 6. Upravleniye gidro-
meteorologicheskoy sluzhby (UOMS) (for Martynov, Simonov, Ivanov,
Bessonov).

(Meteorology--Observers' manuals)

VOLOKH, V.G.; GUSHCHINA, M.V.; IGRUNOV, V.D.; MECHAYEV, I.M.; POKROVSKAYA, I.A.; TRIFONOVA, T.S.; TSYGANOVA, A.M.; RUSIN, N.P., *otv.red.*; KITAYTSY, A.M., *red.*; KUZ'MIN, L.A., *red.*; OLIMPOV, V.G., *red.*; SKITAYKIN, I.S., *red.*; BERLIN, I.A., *red.*; MECHAYEV, I.M., *red.*; SHERBAKOVA, L.F., *red.*; MARTYNOV, S.I., *red.*; SIMONOV, I.S.P., *red.*; IVANOV, A.P., *red.*; BESSONOV, N.P., *red.*; YASHOORODSKAYA, M.M., *red.*; VLADIMIROV, O.G., *tekhn.red.*

[Directions for hydrometeorological stations and posts] *Nastavlenie gidrometeorologicheskim stantsiham i postam. Leningrad, Gidrometeor.izd-vo. No.3, pt.1. [Observations at meteorological stations] Meteorologicheskie nabludeniya na stantsiyakh. 1958. 223 p.*

(MIRA 12:12)

1. Russia (1923- U.S.S.R.) *Glavnoye upravleniye gidrometeorologicheskoy sluzhby.* 2. *Sotrudniki Metodicheskogo otdela Glavnoy geofizicheskoy observatorii im. A.I.Voyeykova (for Volokh, Gushchina, Igrunov, Mechayev, Pokrovskaya, Trifonova, Tsyganova).* 3. *Glavnoye upravleniye Gidrometeorologicheskoy sluzhby SSSR (GUMS)(for Kitaytsy, Kuz'min, Olimpo, Skitaykin).* 4. *Glavnaya geofizicheskaya observatoriya (GGO) (for Berlin, Mechayev, Rusin, Sherbakova).* 5. *Nastnyye upravleniya Gidrometeorologicheskoy sluzhby (for Martynov, Simonov, Ivanov, Bessonov).*

(Meteorology—Observations)

SELYAROV, Viktor Mironovich; KITAYTSEV, A.M., otv.red.; PROTOPOV,
V.S., red.; KHAYNINA, N.I., tekhn.red.


[Meteorology and meteorological observations; a popular course]
Meteorologiya i meteorologicheskie nabludeniya; obshchedostupnyi
kurs. Leningrad, Gidrometeor.izd-vo, 1960. 368 p.

(MIRA 14:2)

(Meteorology)

~~KITAYTSKY~~, G.P. inzhener, [deceased]; KOSOROTOV, I.V., inzhener; TULLAYEV, I.P., inzhener; FRUMKIN, F.D., inzhener; YAKOVLEV, V.N., inzhener, redaktor; TURKOV, G.A., inzhener, redaktor; TIKHONOV, A.Ya., tekhnicheskii redaktor

[Assembling machine tools; a concise reference manual] Montazh metallorazbushchego oborudovaniia; kratkoe spravochnoe posobie. Moskva, Gos. nauchno-tekhn. izd-vo mashinostroit. lit-ry, 1956. 123 p. (Machine tools) (MLRA 10:3)



GA

RITAYTSEV, V. A.

1

New method of measuring the temperature of the external surface of a rotary fan. V. A. Ritaytsev and P. V. Belov, *Trudy Vuzov, No. 8, 1952, 1953*. The temp. is measured by means of a specially constructed thermocouple one terminal of which is a pointed Pt rod and the other 2-3 cm. constant wire welded to the fan shell at regular intervals. The circuit is completed through leads, galvanometer, and cold end.

1952

ZHILIN, A.I.; KITAYTSEV, V.A., redaktor; SHPAYER, A.L., redaktor;
DVORNIKOVA, N.I., tekhnicheskii redaktor.

[Mineral wool] Mineral'naya vata. Pod red. V.A. Kitaitseva.
Moskva, Gos. izd-vo lit-ry po stroit. materialam, 1953. 234 p.
(Mineral wool) (MLRA 7:?)

KITAYTSKY, Y.A.; GURVICH, R.M.; KOROL'KOV, I.V.; OINZBURG, D.B., doktor
tekhnicheskikh nauk, professor, rezensent; NOKHRATYAN, K.A.,
kandidat tekhnicheskikh nauk, nauchnyy redaktor; SOKOL'SKIY, I.P.,
redaktor; LYUBKOVSKAYA, N.I., tekhnicheskiy redaktor

[Heat engineering and heating installations in the building materials
industry] Teplotekhnika i teplovye ustanovki v promyshlennosti
stroitel'nykh materialov. 3-e izd. perer. i dop. Moskva, Gos. izd-vo
lit-ry po stroitel'nykh materialam, 1954. 495 p. (MIRA 8:4)
(Heat engineering) (Building materials industry)

KITATSEY, Vladimir Andreyevich; IVANOV, O.M., kand.tekhn.nauk, nauchnyy
red.; GOMOZOVA, N.A., red.isd-va; EL'KINA, N.M., tekhn.red.

[Technology of thermal insulation materials] Tekhnologiya teplo-
isoliatsionnykh materialov. Moskva, Gos.isd-vo lit-ry po stroit.,
arkhit. i stroit.materialam, 1959. 349 p. (MIRA 13:3)
(Insulation (Heat))

POLUKHIN, P.I., prof., doktor tekhn.nauk, red.; GRINBERG, B.G., dotsent, kand.tekhn.nauk; KANTENIK, S.K., dotsent, kand.tekhn.nauk; ZHADAN, V.T., dotsent, kand.tekhn.nauk; VASIL'YEV, D.I., dotsent, kand.tekhn.nauk; LEBENOV, B.G., dotsent, kand.tekhn.nauk, nauchnyy red.; LAKHTIN, Yu.M., prof., doktor tekhn.nauk, retsentsent; KITAYTSEV, Y.A., dotsent, kand.tekhn.nauk, retsentsent; RAZYGRAYEV, A.M., inzh., retsentsent; YUDINA, L.A., red.isd-vs; RYAZANOV, P.Ye., tekhn.red.

[Technology of metals] Tekhnologiya metallov. Pod obshchey red. P.I.Polukhina. Moskva, Gos.isd-vs lit-ry po stroit., arkhit. i stroit.materialam, 1960. 460 p.

(MIRA 14:3)

1. Kafedra metallovedeniya Moskovskogo avtomobil'no-dorozhnogo instituta (for Lakhtin, Kitaytsev, Razygrayev).
(Metals) (Metalwork)

KITAYTSEV, V. A.

Doc Tech Sci - (diss) "Technology of heat-insulating materials."
Moscow, 1961. 32 pp; (Ministry of Higher and Secondary Special-
ist Education RSFSR, Moscow Order of Labor Red Banner Construc-
tion Engineering Inst imeni V. V. Kuybyshev); 220 copies; price
not given; (KL, 6-61 sup, 211)

KAL'YANOV, Nikolay Nikolayevich; MERZLYAK, Abram Naumovich; KITAYTSEV,
V.A., red.; TYUTYUNIK, M.S., red. izd-va; TEMKINA, Ye.L., tekhn. red.

[Vermiculite and perlite: porous aggregates for insulating articles
and concretes] Vermikulit i perlit - poristyie zapolniteli dlia teplo-
izolatsionnykh izdelii i betonov. Pod red. V.A.Kitaitseva. Moskva,
Gos.izd-vo lit-ry po stroit., arkhit.i stroit. materialam, 1961. 153 p.
(MIRA 14:12)

(Vermiculite) (Perlite (Mineral)) (Insulating materials)

KHIGEROVICH, M.I., doktor tekhn. nauk, prof.; MERKIN, A.P., inzh.;
KITAYTSEV, V.A., kand. tekhn. nauk, dots., retsenzent;

[Intensification of the making of cellular concrete by using vibration] Intensifikatsiia izgotovleniia iacheistykh betonov putem primeneniia vibrirovaniia; doklad na seminare prepodavatelei i aspirantov stroitel'no-tekhnologicheskogo fakul'teta i na XX nauchno-issledovatel'skoi konferentsii instituta. Moskva, Mosk. inzhenerno-stroitel'nyi in-t im. V.V. Kuibysheva, 1961. 14 p. (MIRA 15:11)

1. Zaveduyushchii kafedroy tekhnologii teploizolyatsionnykh materialov (for Kitaytsev). (Lightweight concrete) (Vibrated concrete)

KHIGEROVICH, M.I., doktor tekhn. nauk, prof.; LOGGINOV, G.I., doktor
khim. nauk, prof.; MERKIN, A.P., inzh.; FILIN, A.P., aspirant;
KITAYTSEV, V.A., kand. tekhn. nauk, ispolnyayushchiy obyaz.
prof., reitsenzent

[Vibration-inflated gas concrete; manufacture, macrostructure,
and technical characteristics. Reports at the 22d Research
Conference] Vibrovspuchennyi gasobeton; izgotovlenie, makro-
struktura i tekhnicheskie svoistva. Doklady na XXI nauchno-
issledovatel'skoi konferentsii. Moskva, 1962. 19 p.

(MIRA 17:4)

1. Moscow. Inzhenerno-stroitel'nyy institut. 2. Zaveduyushchiy
kafedroy tekhnologii teploizolyatsionnykh materialov Moskovskogo
inzhenerno-stroitel'nogo instituta (for Kitaytsev). . .

KITAYTSEV, Vladimir Andreyevich

[Technology of heat-insulating materials] Tekhnologiya
teploizolatsionnykh materialov. Izd.2., perer. i dop.
Moskva, Stroiizdat, 1964. 403 p. (MIRA 17:6)

BARBARINA, T.M.; HUBYR', N.F.; BUTT, L.M.; VEL'SOVSKIY, V.N.;
 GORLOV, Yu.P.; GRIBANOVSKIY, V.G.; DROZDOV, I.Ya.;
 YEREMIN, I.A.; ZEZIN, V.G.; KEVESH, P.D.; KOCHAROV, E.P.;
 KOSYREVA, Z.S.; LEVIN, S.N.; MAKHOVICH, A.T.; MERZLYAK,
 A.N.; RODOV, E.S.; ROZIMOV, A.I.; SEREBRYANSKAYA, B.I.;
 SUKHAREV, M.F.; USTENKO, A.A.; KHOMENKO, Z.S.; SHMIDT,
 L.M.; ETIN, A.O.; YAKHONTOVA, N.Ye.; KITAYISEV, Vladimir
 Andreyevich, prof., doktor tekhn. nauk, red.; SKRAMTAYEV,
 B.G., glav. red.; TROKHIMOVSKAYA, I.P., zam. glav. red.;
 KRAVCHENKO, I.V., red.; KITAYGORODSKIY, I.I., red.;
 KRZHEMINSKIY, S.A., red.; ROKHVARGER, Ye.L., red.; BALAT'YEV, P.K.
 red.

[Manual on the manufacture of heat insulating and acous-
 tical materials] Spravochnik po proizvodstvu teploizo-
 liatsionnykh i akusticheskikh materialov. Moskva, Stroi-
 izdat, 1964. 524 p. (MIRA 18:1)

KITAYTSEV, V.A., prof., doktor tekhn. nauk ; KHAYTER, S.P., inzh.

Book about perlite. Stroi. mat. 10 no.9:40 -p.3 of cover 3 '64
(KIRA 18:2)

KITAYTSNV, Ya.

Preparing windows and doors for the winter season. Zhil.-
kom.khos. 9 no.10:30-31 '59. (MIRA 13:2)
(Windows) (Doors)

NESOV, V.D., inzh., red.; ~~KITAYTSEVA, L.S.~~ inzh., red.; STRASHNYKH,
V.P., red.izd-va; RODIONOVA, V.M., tekhn. red.

[Construction specifications and regulations] Stroitel'nye
normy i pravila. Moskva, Gosstroizdat. Pt.2. Sec.L.ch.7.
[Specifications for the design of stores] Magaziny; normy
proektirovaniia (SNiP II-L. 7-62). 1962. 21 p.

(MIRA 16:12)

1. Russia (1923- U.S.S.R.) Gosudarstvennyy komitet po de-
lam stroitel'stva. 2. Gosudarstvennyy komitet Soveta Mi-
nistrov SSSR po delam stroitel'stva (for Nesov). 3. Gosudar-
stvennyy institut po proyektirovaniyu predpriyatiiy torgovli
i obshchestvennogo pitaniya (for Kitaytseva).

(Stores, Retail)

KITAITSEVA, V.P. [Kytaitseva, V.P.], insh.

Row crop cultivator for sugar beets. Mekh. sil'. hosp. [9]
no.5:29-30 My '58. (MIRA 11:6)
(Sugar beets) (Agricultural machinery)

KITAYTSOVA, Z.P. [Kytaitsova, Z.P.], insh.

For further improvement of machinery for harvesting sugar beets.
Makh. sil'. hosp. 9 no. 7:17-19 J1 '58. (MIRA 11:8)
(Sugar beets--Harvesting)

KUKTA, O.M. KITAYTSEVA, Z.P.

Results of testing new machinery for sugar beet growing.
Mekh. i elek. sots. sel'khoz. 19 no.3:55-59 '61 (MIRA 14:6)

(Agricultural machinery --Testing)(Sugar beets)

BONDARENKO, M.O. [Bondarenko, M.H.]; VORONEZHSKIY, V.I. [Voroneshs'kyi, V.I.]; KITAYTSEVA, Z.P.; KOVAL', M.M.; KOLODA, V.D.; KORSAKOV, O.O.; KREMINSKAYA, Ys.D. [Kremins'ka, M.D.]; KUKTA, O.M. [Kukta, H.M.], inzh.-mekhan.; PIVOVAR, S.G. [Pivovar, S.H.]; SOLOVYI, V.I.; OLEFI-
RENKO, O.A. [Olefirenko, H.A.], red.; OULENKO, O.I. [Hulenko, O.I.],
tekhn.red.

[New agricultural machines] Novi sil's'kohospodars'ki mashyni.
Kyiv, Derzh.vyd-vo sil's'kohospodars'koi lit-ry URSS, 1959. 231 p.
(MIRA 13:4)

(Agricultural machinery)

ANAN'YEV, Sergey Petrovich; KITAYSKIY, Yevgeniy Vladimirovich; NASONOV, Il'ya Dmitriyevich; MEYENBURG, Vadim Yevgen'yevich; PAVLOV, K.V.,
otv. red.; CHECHKOV, L.V., red. 1zd-va; SHKLYAR, S.Ya., tekhn.
red.

[Boring and blasting, driving and supporting of mines] Burovarynyye
raboty, provedeniye i krepleniye gornyykh vyrabotok. By S.P. Anan'ev i
dr. Moskva, Gos. nauchno-tekhn. 1zd-vo lit-ry po gornomu delu,
1961. 355 p. (MIRA 14:9)

(Mining engineering)

(Blasting)

KITAZAWA, O.

Nondestructive testing of wood. p. 347.

FAIPAR. (Faipari Tudományos Egresulet) Budapest, Hungary, Vol. 9, no. 11, Nov. 1959.

Monthly List of East European Accessions (HEAL)LC, vol. 9, no. 1, Jan. 1960.

Uncl.

KITAZAWA, George

Nondestructive testing of wood materials. Faipar 11
no.11:347-350 N '59.

DZHRBASHYAN, M.M., akademik; KITBALYAN, A.A.

Generalization of Chebyshev polynomials. Dokl. AN Arm. SSR 38
no.5:263-270 '64. (MIRA 17:6)

1. Institut matematiki i mekhaniki AN Armyanskoy SSR, 2. AN Armyanskoy SSR (for Dzhrbashyan).

KITBALIAN, A.A.

Expansions in generalized trigonometric systems. Izv. AN Arm.
SSR. Ser. fis.-mat. nauk 16 no.6:3-24 '63. (MIRA 17:8)

1. Institut matematiki i mekhaniki AN Arzyanskoy SSR.

KITBALYAN, A.A.

Orthogonal systems of rational functions and biorthogonal systems
of generalized trigonometric functions. Izv. AN Arm. SSR. Ser. fiz.-
mat. nauk 18 no.4:21-45 '65. (MIRA 18:9)

1. Institut matematiki i mekhaniki AN Armyanskoy SSR.

KITBALYAN, A.A., red.; AKIKENYAN, L.A., tekhn.red.

[Summaries of reports delivered at the Fifth All-Union Conference
on the Theory of Functions] Tesisy dokladov V-i Vsesoiusnoi
konferentsii po teorii funktsii. Izd-vo Akad.nauk Armianskoi
SSR, 1960. 125 p. (MIRA 14;2)

1. Vsesoyuznaya konferentsiya po teorii funktsiy, 5th.
(Functions--Congresses)

KITBALYAN, A.A.

Expansion into biorthogonal systems composed of Volterra functions. Izv. AN Arm. SSR. Ser.fiz.-mat. nauk 14 no.6: 17-47 '61. (MIRA 15:1)

1. Institut matematiki i mekhaniki AN Armyanskoy SSR.
(Series, Orthogonal)
(Functions, Entire)

KITBALYAN, A.A.

Work of the All-Union Conference on the Theory of Functions held
in Erivan. Usp. mat. nauk 16 no.4:241-242 J1-Ag '61. (MIRA 14:8)
(Erivan--Mathematics--Congresses) (Functions)

KITCHENKO, A. V.

32754. BLAGODETEL'NAYA, V. A. i KITCHENKO, A. V. Kharakteristika difteriynykh palochyek, vydelenykh v 1945-46 gg. v khar'kove. Soobshch. v. Trudy ukr. In-ta spidemiologii i mikrobiologii im. Mechnikova, T. XVI, vyp. 1, 1949, s. 129-36

80: Letopis' Zhurnal'nykh Statey, Vol. 44, Moskva, 1949

PALANT, B.L.; BLAGODETEL'NA, V.A.; KITCHENKO, A.V.; OLEJNIKOVA, Ye.A.

Effect of sleep induced by drugs upon the development of certain infections. Zhur.mikrobiol.epid.i immun. no.3:89 Nr '54. (MLRA 7:4)

1. In Khar'kovskogo instituta epidemiologii i mikrobiologii im. Mechnikova i kafedry mikrobiologii Khar'kovskogo instituta usovershenstvovaniya vrachey. (Sleep) (Infection)

AVIATION, ETC.

USSR/Medicine - Pharmacology; Central nervous system and infection

FD-2312

Card 1/1 Pub 148 - 13/36

Author : Gres'-Edel'man, B. Ye.; Zhuk, A. S.; Kitchenko, A. V.

Title : The effects of processes of excitation and inhibition of the central nervous system on the course of experimental streptococci infections

Periodical : Zhur. mikro. epid. i immun. No 2, 38-39, Feb 1955

Abstract : On the basis of the experimental results described, arrive at the following conclusions: white mice (highly susceptible to infection with hemolytic streptococci) are protected by caffeine from death on infection in a considerable percentage of cases, not protected by urethan (death expedited), and not protected by medinal (died at the same time as control animals); while guinea pigs (relatively insusceptible to infection) are made more susceptible by caffeine and protected by urethan.

Institution : Khar'kov Institute of Vaccines and Sera imeni Mechnikov; Chair of Microbiology, Ukrainian Institute of Advanced Training for Physicians

Submitted : July 15, 1954

USSR / Microbiology. Microorganisms Pathogenic to Humans
and Animals.

F-3

Abs Jour : Ref Zhur - Biol., No 8, 1958, No 33824

Author : Shehit, O. R., Kitchenko, A. V.

Inst : Not given

Title : Characteristics of Intestinal Bacilli Isolated from Dysen-
tery Patients and Healthy Individuals. Report 2. Morpho-
logical, Cultural, Fermentative, and Serological Properties
of Intestinal Bacilli Parastrains Isolated from Dysentery
Patients and from Healthy Individuals.

Orig Pub : Sb. rabot po dizenterii, Kharkov, 1956, 13-16.

Abstract : Intestinal bacilli parastrains yielding a positive reaction
of agglutination with Flexner serum type "c" were isolated
from patients in whom the dysentery stimulant was not found
on feces examination. Strains agglutinated by Flexner serum
in high dilutions were virulent to mice. In a portion of

Card 1/2

USSR/Microbiology. Microbes Pathogenic for Man and
Animals

F

Abs Jour : Ref Zhur-Biol., No 13, 1958, 57663

Author : Kitchenko A. V.

Inst : Not given

Title : Characteristic of Coli Bacilli Isolated from
Dysenteric patients and healthy persons. Report
3. Characteristic of Parastrains of the Coli Ba-
cillus Isolated from Patients Ill with Dysentery,
After Passing Through the Organism of White Mice

Orig Pub : Sb. rabot po dizenterii, Kharkov, 1956, 17-25

Abstract : The results of the passing of two strains of the
coli bacillus, isolated from patients ill with
dysentery of an unconfirmed diagnosis, through
the organism of white mice are reported. Both
strains were found to be virulent for mice and to
possess antigens common with the Flexner's type
O dysentery bacillus.

Card 1/1

SKORIKOV, P.A.; KITCHENKO, G.A., master

Organization of material and technical procurement and work
of the order bureau in the locomotive depot in Krasnodar.
Elek. i tepl. tiaga 9 no.11:6-8 N '65.

(MIRA 19:1)

1. Lokomotivnoye depo Krasnodar.

EXCERPTA MEDICA Sec. 17 Vol. 3/11 Public Health Nov. 57

3326. KITCHENKO M.G. - The effective sanitary value of different variants of water-isolated coli organisms (Russian text)
2. MIKROBIOL. 1957, 1 (63-71) Graphs 4

The sanitary significance of various types of coli organisms was investigated, especially its dependence on their biochemical activity, the ability to ferment sugars, the proteolytical ability, the creation of H_2S and their ability to agglutinate. On the basis of experiments made it was found out that the whole group of coliform bacteria can be used as indicators of faecal pollution of water. Three characteristics are decisive for the determination of their faecal origin: (1) the resistance against certain concentrations of rosolic acid (aurine) in the medium, (2) the ability to ferment glucose at $43^{\circ}C$. and lactose at $37^{\circ}C$., (3) the polymorphous rods are Gram-negative.

Symon - Prague (XVII, 4°)

AUTHOR: Kitchenko, N.A., Mining Engineer SOV-127-58-8-17/27
TITLE: Delivery of Props into the Pits by Pipe (Transportirovka krepzhnogo lesa v shakhtu po trubam)
PERIODICAL: Gornyy zhurnal, 1958, Nr 8, p 68 (USSR)
ABSTRACT: The author describes the delivery of mine props into the pits through the pipes installed in vertical shafts in East Germany. There is 1 diagram.
1. Mines--Equipment 2. Pipes--Applications 3. Mining engineering

Card 1/1

KITCHENKO, N.A.

Device for sliding timbering into the "Novaya" Mine of the
Rosa Luxemburg Mining Enterprise. Kolyma 21 no.2:7-8 P '59.
(MIRA 12:7)

1. Nauchno-issledovatel'skiy gornorudnyy institut.
(Krivoy Rog--Mine timbering)

G. KITCHINGAM

"An Outline of French Forestry Literature. p. 98" (SUMARSKI LIST, Vo. 77,
No. 2, Feb. 1953, Zagreb, Yugoslavia)

SO: Monthly List of East European Accessions, L.C., Vol. 2, No. 11,
Nov. 1953, Uncl.

KITSLADZ, Y.S.; KPSHTAYN, F.G.; ALEKSEYEVA, A.A.; SOROKINA, Ye.Yu.;
KHAZAEVA, L.D.; LOZHKINA, A.N.; ZAKSTEL'SKAYA, L.Ya.; KHARAKHASH'YAN,
K.T.

Clinical and virological study of influenza during the 1959 winter
outbreak. Vop. virus. 6 no.5:629-630 '61. (MIRA 14:1)

1. Institut virusologii imeni D.I.Iyanovskogo AMN SSSR, Moskva.
(INFLUENZA)

KOCHL', P.O.; KITYENKO, A.I.

On the continuity of kinematic links when switching transmissions
by central control mechanisms. Stan.i instr. 26 no.9:5-10 8 '55.
(Machinery, Kinematics of)

KITENKO, L.A.

Reducing the thickness of the body and connecting-pipes of scrubbers.
Suggested by L.A. Kitenko. Rats. predl. no. 44:9 '59.

(Scrubber (Chemical technology)) (MIRA 14:1)

KITENKO, V. A.

PA-23T42

Sep 1967

"Modernization of Fine Boilers," V. A. Kitenko, 1967

"In Zhurnal Topliva" Vol. IV, No 9

The author gives a very general description of modernization of fine boilers and states that he is unable to give any more definite ideas because of the factors involved: type of boiler, type of fuel and how it is burned, quality of the water used in the boiler, the construction of existing fine boilers and the construction of these fine boilers.

23T42

KITENKO, V.S.

UCHYUMOV, B.L.; ROZHESTVENSKIY, V.M.; RUDNEV, O.P.; AGAFONOV, V.I.;
KULAGIN, S.M.; KUCHERENKO, V.D.; *KITENKO, V.S.*

Andrei Iakovlevich Alymov, d.1965; obituary. Zhur. mikrobiol.,
epid. i immun. 42 no.8:156-157 Ag '65. (MIRA 18:9)